

Chateau


**BLUE
DAWN**

Technical Specifications


Total Thickness	6 mm	Backing	IXPE
Wear Layer Thickness	0.5 mm (20 mil)	SQ. FT. / Box	22.70 SQ. FT.
Size	9" x 60" x 6 mm	Pcs / Box	6

Installation Methods


Tile laying patterns



Brick formation




Deck formation




Straight lay

Plank laying patterns



Brick bond



45° angle

Certifications



Additional Information

All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product Specifications may be changed without notice as long as product performance is not materially affected.

Chateau Testing

Item	Standard / Requirements	Result
Material		100% Virgin PVC
Performance Classification	EN685	23,31
Peeling Strength of Layer	EN431	>50N / 50mm
Dimension Stability	EN ISO23999:2012	<0.04
After Exposure to Heat		
Curing After Exposure to Heat	EN434	<1.2 mm
Residual Indentation	EN ISO24343-1:2012	<0.01 mm
Fire Resistance	EN ISO92391-1 / EN ISO11925-2	Bfl-S1
Color Fastness to Light	ISO105 B02	Grade>6
Flexibility	EN435	Pass
Abrasion Resistance	EN660	Class T
Castor Chair Resistance	EN425	Pass
Slip Resistance	DIN 51130 / EN 13893	R9 / Class DS
Formaldehyde Emission	EN717-1/EN14041	Class E0
Chemical Resistance	EN423	Pass
Acoustic Impact Noise Reduction	ASTM E492-09/E 989-06	IIC=69
Electrical Behavior Body Volt	AATCC134-1996	Pass
Thermal Conductivity	ISO8302	0.0245m2/tin.ft
Dimensional Stability	ASTM F2199	Pass
Recycling		Suitable 1000 PSI
Static Load	ASTM F137	

- UV-coating surface finish
- Glueless click system for fast installation as easy as laminate
- Luxurious embossing and natural look of wood plank flooring
- 100% waterproof resilient flooring that can be used anywhere in home or commercial areas
- Foundation must be level before installation
- Simple to clean: damp mop, sweep or vacuum
- Durable, stable, and eco-friendly; Low VOC emission, no toxicity, 100% recyclable
- 25 years Residential Limited Warranty
- 5 years Light Commercial Limited Warranty